



ard f.lli raccanello s.p.a. industria vernici e smalti

TECHNICAL SHEET **114**

CODE 0.503.

aedilia

Washable emulsion paint

GENERAL PROPERTIES

AEDILIA is an emulsion paint devised on innovative criteria which offers good qualities in general & an effortless application.

It offers an optimum "whiteness", good hiding power & washability. The special synthetic polymers in emulsion provide a good scrub resistance, ease of application & flow.

These features together with an appealing satiny effect make AEDILIA a quality finish for interiors.

INSTRUCTIONS

Substrate preparation:

- Bare interior walls: use a soft brush to remove dust & unsound plaster. Level any imperfections with LITOSTUCCO 1.050.1010 or SILVER STUCK 1.963.1010 adding as many times as necessary. Allow 6 hrs, sand the stuccowork & clean accurately. Seal the whole surface with a hand of ISOLEX W or ARDFIX thinned (1 part in 8 parts of water). Allow 4 or 12 hrs respectively & apply 2 hands of AEDILIA.
- Interiors with distemper paintwork: clean accurately & stucco any imperfections with LITOSTUCCO as indicated above. Sand, seal the whole surface with a hand of ISOLEX W or ARDFIX. Allow 12 hrs & apply AEDILIA.
- Interiors with washable emulsion paintwork: clean accurately, stucco any imperfections, sand & dust. Seal the stucco work with a hand of ISOLEX W or ARDFIX. Allow 4 hrs & proceed with AEDILIA.

Application:

Apply AEDILIA as follows:

- Brush: stir well, dilute at 30-40% in water volume & apply by cross brushing. Allow 2-3 hrs & proceed with the second hand thinning AEDILIA at 30-35% in water volume.
- Roller: dilute at 15-20% in water volume.
- AEDILIA is easy to tint using IDROPAINT 502, high concentration colorants COLORATUTTO 0.951 & ARDCOLOR 2.950.
- Store in cool, frost free, premises. Do not apply at a temperature below +5°C or above +35°C.
- Wash equipment immediately after use with water.
- AEDILIA is compatible with the 16COLOURS & WIZARD tinting systems.

- Use products in compliance with the current Health & Safety Regulations. Dispose of spent material/containers according to the same.
- Refer to the PSDS for further details.

TECHNICAL PROPERTIES

| | | |
|--------------------|-----------------|---------|
| SPECIFIC WEIGHT | 1560 ÷ 50 g/l | |
| VISCOSITY AT 20 °C | 15000 ± 2000 cp | |
| ASPECT OF FILM | Satin | |
| COLOUR | White | |
| DRYING AT 20 °C | TOUCH DRY | 2 hrs |
| | THROUGH DRYING | 24 hrs |
| WASH RESISTANCE | EN 13300 | Class 3 |

YIELD

A two coat cycle implies a yield of 5,5 - 6 m²/l.

TENDER SPECIFICATION ITEM

WASHABLE EMULSION PAINT

Application on treated surfaces of two layers of highly covering emulsion paint based on synthetic copolymers in aqueous dispersion & colouring pigments type AEDILIA, with a min consumption of 0,18 l/m².

€/m²

The data herein were correct at the time of Quality Control & refer to standardized environmental conditions. The same are to be considered as a guide.

Revision 2015/06



ard · f.lli raccanello s.p.a. · industria vernici e smalti

35129 PADOVA – Zona Ind.le Nord 1ª Strada, 13 – Tel. 049.8060000 (5 linee)

Fax 049.773749 – www.ard-raccanello.it - E-mail: ardspa@ard-raccanello.it