



ard f.lli raccanello s.p.a. industria vernici e smalti

TECHNICAL SHEET **134**

CODE 0.073

creative fondo

Uniforming primer for decorative products

GENERAL PROPERTIES

CREATIVE FONDO is a smooth pigmented primer based on copolymers in aqueous dispersion which make it the perfect top coat for the CREATIVE line of decorative products.

CREATIVE FONDO offers an optimum bond to mineral surfaces & appealing aesthetics unrealizable with normal latex paints. Its brushability, covering & uniforming power are remarkable and it is also odourless.

INSTRUCTIONS

Substrate preparation:

- Unsound surfaces: use a soft brush to remove dust and unsound plaster. Level any imperfections with LITOSTUCCO adding as many times as necessary. Allow 4 hrs & apply a hand of ISOLEX W or ARDFIX. Allow a further 6 hrs before applying CREATIVE FONDO.
- Bare interior surfaces & distemper paintwork: use a soft brush to remove dust and unsound plaster. Level any imperfections with LITOSTUCCO adding as many times as necessary. Allow 6 hrs, sand the stuccoed areas and clean thoroughly. Seal & uniform the whole surface with a two hands of CREATIVE FONDO.
- Interior surfaces with washable latex paintwork: clean thoroughly, stucco any imperfections, sand & dust. Seal the stuccoed areas with a two hands of CREATIVE FONDO.

Application:

Apply CREATIVE FONDO as follows:

- **Brush:** stir well, thin at 25-30% in water volume and apply in a cross-wise fashion. Apply the second hand after 4 hrs.
- **Roller:** stir well, thin at 15-20% in water volume and apply in a cross wise fashion. Allow 4hrs before applying the second hand.
- CREATIVE FONDO can be recoated with the desired top coat 8 hrs after drying.
- Store in cool, frost free premises.

- Do not apply if humidity is excessive or ambient/substrate temperatures are below +5°C or above +35°C.
- Wash equipment immediately after use with water.
- CREATIVE FONDO is easy to tint with the 16COLOURS & WIZARD pastes. Refer to the specific hue indicated in the colour show card when using this product as a primer for CREATIVE SETARD.
- Use in compliance with current Health & Safety Regulations. Dispose of spent material/containers according to the local regulations. Refer to the PSDS for further details.

TECHNICAL PROPERTIES

SPECIFIC WEIGHT	1520 ± 50 g/l	
VISCOSITY AT 20°C	9.000 ± 2000 cP	
COLOUR	White	
ASPECT	Flat	
DRYING AT 20 °C	TOUCH DRYING	2 hrs
	THROUGH DRYING	24 hrs

YIELD

A two layer painting cycle implies a yield of approx. 7 m²/l. Said yield refers to smooth surfaces with medium absorption. We recommend testing on the specific substrate.

TENDER SPECIFICATION ITEM

UNIFORMING PRIMER FOR DECORATIVE PRODCUTS

A two layer application on treated surfaces of pigmented filler primer specific for interior/exterior decorative products type CREATIVE FONDO with a minimum consumption of 0,14 l/m².

€/m²

The data herein were correct at the time of Quality Control and refer to standardized environmental conditions. The same are to be considered as a guide.
Revision 2015/06



ard · f.lli raccanello s.p.a. · industria vernici e smalti

35129 PADOVA – Zona Ind.le Nord 1ª Strada, 13 – Tel. 049.8060000 (5 linee)
Fax 049.773749 – www.ard-raccanello.it - E-mail: ardsipa@ard-raccanello.it