



# ard f.lli raccanello s.p.a. industria vernici e smalti

TECHNICAL SHEET **177**

CODE 0.074.

## primer murale

Mineral based neutralizer for interior & exterior walls

### GENERAL PROPERTIES

PRIMER MURALE is a particular product based on mineral salts & specific additives in a concentrated aqueous solution. Its versatile performance offers an optimum solution to the most common problems such as:

**Patching:** PRIMER MURALE is ideal for the pre-treatment of surfaces with patches of smoke, nicotine, soot, damp etc.

**Sealing:** optimum combination of penetration & impregnation reducing the surfaces' absorption.

**Consolidation:** the crystallization of the salts in the plaster's capillary network arrests the chalking & decaying process of mineral surfaces.

PRIMER MURALE is suitable for interior & exterior surfaces in cement/lime plaster, plaster of Paris, plasterboard & old sound paintwork.

### INSTRUCTIONS

#### Substrate preparation:

- Bare walls: ensure the wall has weathered for at least 28 days. Clean thoroughly, removing dust, filth & any unsound parts.

#### Application:

Apply PRIMER MURALE as follows:

- PRIMER MURALE can be applied neat using a brush or spray. We recommend thinning at 100% with water when treating surfaces with poor absorption.
- When neutralizing patches, the impregnation of the margins of the compressed areas require particular attention.
- Treat gypsum & plasterboard with two hands of PRIMER MURALE wet on wet.
- During application protect any metal objects, marble & glass,
- After application exterior surfaces must be protected against rain for at least 24 hrs.
- When applying on painted surfaces any excess will deposit a powder which must be removed before recoating.
- Do not apply at ambient/substrate temperatures below +5°C or above +30°C.
- Use in compliance with current Health & Safety Regulations. Dispose of spent material/containers according to the same.

---

**TECHNICAL PROPERTIES**

SPECIFIC WEIGHT	1200 ± 30g/l
NATURE OF BINDER	mineral
THINNER	water
DILUTION % BY VOLUME	0 – 100%
	neat
RECOATABLE	24 hrs

---

**YIELD**

The yield varies according to the absorption of the substrate; 8-10 m<sup>2</sup>/l is an approx guide.

---

**TENDER  
SPECIFICATION ITEM****MINERAL BASED NEUTRALIZER FOR INTERIORS & EXTERIORS**

Brush/spray application on treated surfaces of a int/ext neutralizer for based on mineral salts & specific additives which seal, consolidate & neutralize the substrate preserving the mineral characteristics of the surface type PRIMER MURALE with a minimum consumption of 0,10 l/m<sup>2</sup>.

€/m<sup>2</sup>

---

The data herein were correct at the time of Quality Control and refer to standardized environmental conditions. The same are to be considered as a guide.  
Revision 2012/07



**ard · f.lli raccanello s.p.a. · industria vernici e smalti**

35129 PADOVA – Zona Ind.le Nord 1<sup>a</sup> Strada, 13 – Tel. 049.8060000 (5 linee)  
Fax 049.773749 – [www.ard-raccanello.it](http://www.ard-raccanello.it) - E-mail: [ardspa@ard-raccanello.it](mailto:ardspa@ard-raccanello.it)