



ard f.lli raccanello s.p.a. industria vernici e smalti

TECHNICAL SHEET **31**

CODE 0.025

base

Undercoat for wood and iron

GENERAL PROPERTIES

BASE is an anticorrosive filler paint for interior/exterior iron & wooden surfaces.

It features excellent filling & spreading power, good adherence, sanding & surface/through drying.

Its anti corrosion properties make it the ideal product for application on iron/cast iron (e.g., radiators).

The mould resistant additives employed also protect wooden surfaces.

INSTRUCTIONS

Surface preparation:

- Woodwork: remove unsound paintwork by sanding. Stucco any imperfections (knots, joints, rivets, cracks etc.) with a synthetic stucco, or, for indoors with LITOSTUCCO 1.050.1010, adding as many times as necessary. Allow 24 or 6 hrs respectively, sand repair areas, clean and apply a coat of BASE. Allow 24 hours, sand the whole surface with fine sandpaper, clean thoroughly and, if necessary, apply a second coat of BASE. Allow 24 hours & finish with two coats of gloss enamel (Neoard 0.154., Tema 0.135., or Ardeol 0.151.) or satin-finish (Ardsilk 0.250.or Tema 0.235.).
- Ironwork & cast iron: remove any unsound paintwork and/or flaking metal using a wire brush and emery cloth. Clean the whole surface thoroughly & apply one or two coats of BASE. Allow 24 hrs, sand the surface with fine sandpaper, clean thoroughly and, if necessary, apply a second coat of BASE. Apply the finishing enamel after 24 hrs.

Application:

Apply BASE as follows:

- Brush: stir well, thin at 6-8% in volume with Diluente ARD 0.970.0030 & apply in thin coats. Allow at least 12 hours between coats.
- Compressed air spraying: use 8% (max) in volume of Diluente ARD 0.976.0040 & appropriate apparatuses. Allow at least 12 hours between coats.
- To avoid *removal*, never recoat BASE with products thinned using nitre based diluents.
- BASE can be tinted using ARD's glossy/silky alkyd enamels or with universal COLORATUTTO colorants 0.951.

- During application, especially when spraying, ensure the room is aired correctly.
 - Wash equipment with the ARD 0.970.0030 thinner immediately after use.
 - The product is flammable. Use in compliance with the current Health & Safety Regulations. Dispose of spent material/containers according to the same.
- Refer to the PSDS for further information.

TECHNICAL PROPERTIES

SPECIFIC WEIGHT	1415 ± 50 g/l	
VISCOSITY AT 20°C	43 ± 3s DIN Cup n° 6	
SOLID CONTENT BY VOLUME	50-52%	
APPEARANCE OF FILM	matt	
COLOUR	white	
SANDING	after min. 12 hrs	
DRYING AT 20°C	DUST FREE	2 hrs
	TOUCH DRY	3-4 hrs
	THROUGH DRYING	48 hours
FLASH POINT	+39° C	

YIELD

1 coat (40 micron thick) implies a coverage of approximately 11 m²/l.
Said thickness can be achieved with 1 coat using a brush or compressed air spraying.

TENDER SPECIFICATION ITEM

WOOD & IRON UNDERCOAT

Anticorrosive fungicidal matt paint with excellent filling properties for wood & iron.

Application of 1 or 2 coats on pretreated surfaces, of anticorrosive filling undercoat for wood & iron type BASE 0.025.1010 for interiors/exterior, with a minimum consumption of 0.10 l/m².

€/m²

The data herein were true at the time of Quality Control and refer to standardized environmental conditions. The same are to be considered as a guide.

Revision 2012/07



ard - f.lli raccanello s.p.a. - industria vernici e smalti

35129 PADOVA – Zona Ind.le Nord 1ª Strada, 13 – Tel. 049.8060000 (5 linee)
Fax 049.773749 – www.ard-raccanello.it - E-mail: ardspa@ard-raccanello.it