



ard f.lli raccanello s.p.a. industria vernici e smalti

TECHNICAL SHEET **41**

CODE 1.057.1010

idrostucco

Rapid filler for walls

GENERAL PROPERTIES

IDROSTUCCO is an easy, spatulable soft thin stucco which offers a good filling power, quick drying, effortless ease of sanding & reduced shrinkage.

Its specific for the filling of interior plasters & old painted orange peel coatings. It's the perfect product for food industries which comply with the Regulation (EC) 852/2004 (HACCP protocol) as it guarantees an excellent level of cleaning & disinfestation.

INSTRUCTIONS

Substrate preparation:

Interior two-coat plaster work: clean thoroughly, ensure the surface is dry & apply, adding as many times as necessary, IDROSTUCCO using a float. Allow 6 hrs fill, sand any imperfections, clean accurately & seal with a hand of ARDFIX 0.070 or BIANCOFIX 0.079. Allow 4 hrs & apply the finishing product.

Painted walls: IDROSTUCCO normally guarantees an optimum adhesion on old glossy coatings & traditional enamels. However, due to the vast & various conditions of the substrates we recommend testing & sanding. All surfaces must be perfectly clean, free of oil and grease. IDROSTUCCO has been devised to enhance the ARD line of water-dilutable enamels (TEMA line - IDROSMALTO line) resulting in aesthetically pleasing & functional surfaces.

Application:

IDROSTUCCO is ready for use & can be applied using a float or spatula. If necessary it can be thinned using a small amount of water. Apply by filling, as many times as necessary, in thin layers at 1 hr intervals. The recommended thickness is 0,5 mm per layer. Allow 6 hrs & sand.

- Do not apply under direct sunlight or at ambient temperature below + 5°C. or above + 35°C.
- Wash equipment immediately after use with water.
- Store in a cool premises under frost proof conditions.

- Use products in compliance with current Hygiene & Safety Regulations. Dispose of spent material/containers according to the same.

Refer to the PSDS for further details.

TECHNICAL PROPERTIES

SPECIFIC WEIGHT	1680 ± 50 g/l	
COLOUR	White	
SANDING	After 6 hrs	
DRYING AT 20 °C	TOUCH DRYING	1 hr
	THROUGH DRYING	8 hrs

YIELD

A 0,5 mm dry layer of IDROSTUCCO implies a yield of 1 m²/kg.

SPECIFICATIONS

RAPID FILLER FOR WALLS

Application of spatulable water based filling stucco based on synthetic resins in aqueous dispersion & inert fillers type IDROSTUCCO with an approx min. consumption of 2,5 kg/m².

€/m².

The data herein were correct at the time of Quality Control and refer to standardized environmental conditions. The same are to be considered as a guide.

Revision 2014/10



ard · f.lli raccanello s.p.a. · industria vernici e smalti

35129 PADOVA – Zona Ind.le Nord 1ª Strada, 13 – Tel. 049.8060000 (5 linee)

Fax 049.773749 – www.ard-raccanello.it - E-mail: ardspa@ard-raccanello.it