



# ard f.lli raccanello s.p.a. industria vernici e smalti

TECHNICAL SHEET **42**

CODE 1.963.0010

## **silver stuck**

Self adhesive filler stucco powder for the building industry

### **GENERAL PROPERTIES**

SILVER STUCK is a stucco powder based on a particular variety of gypsum & synthetic polymers in powder.

SILVER STUCK is suitable as a filler for interior plaster, static cracks & holes before painting. It's the perfect product for stuccowork on plasterboard.

Mixed with water it provides a soft stucco which is extremely easy to apply & sand. SILVER STUCK is also successfully used to apply plaster of Paris decorations such as ceiling roses, cornices etc.

### **INSTRUCTIONS**

#### **Stucco preparation:**

Add 2 parts of SILVER STUCK to 1 part of water. Slowly stir the mixture until the paste is smooth, then leave to set for about 10 minutes. The product is "workable" for over an hour.

#### **Substrate preparation:**

Interior two coat plaster work/gypsum walls: thoroughly clean the areas to be stuccoed (holes, cracks etc.), dampen & apply SILVER STUCK adding as many times as necessary. Allow 6 hrs, fill & sand the stuccowork, clean accurately & seal the whole surface with a hand of ISOLEX W or BIANCOFIX. Allow 4 hrs & finish with an ARD emulsion paint (IDROPAINT - AEDILIA - TRASPIRA etc.).

#### **Application:**

Amalgamate SILVER STUCK with the necessary amount of water: Apply as a base coat for the subsequent layers with a 1mm (max) thickness. Allow 6 hrs & dry sand. Drying depends on the ambient temperature, R.H. & the thickness of the paste.

- Do not apply under direct sunlight or at ambient/substrate temperature below + 5°C. or above + 35°C.

- Wash equipment immediately after use with water.
- The product does not require a WARNING label in compliance with current regulations.

Refer to the PSDS for further details.

## TECHNICAL PROPERTIES

ASPECT	White powder
DILUTION WITH WATER	2 : 1
SANDING	After 6 hrs
DRYING AT 20 °C 1MM LAYER	30 mins

## YIELD

A 1 mm dry layer of SILVER STUCK implies a yield of 2 m<sup>2</sup>/kg.

## SPECIFICATIONS

### SELF ADHESIVE FILLER STUCCO POWDER FOR THE BUILDING INDUSTRY

Application on pretreated interior mineral surfaces of stucco filler powder based on gypsum & synthetic polymers mixable with water - for filling on plaster, static cracks & holes - with a 1mm thickness per layer, effort free sanding type SILVER STUCK. Consumption per millimetre of 0,5 kg/m<sup>2</sup>.

€/m<sup>2</sup>.

The data herein were correct at the time of Quality Control and refer to standardized environmental conditions. The same are to be considered as a guide.

Revision 2015/06



**ard · f.lli raccanello s.p.a. · industria vernici e smalti**

35129 PADOVA – Zona Ind.le Nord 1ª Strada, 13 – Tel. 049.8060000 (5 linee)

Fax 049.773749 – [www.ard-raccanello.it](http://www.ard-raccanello.it) - E-mail: [ardspa@ard-raccanello.it](mailto:ardspa@ard-raccanello.it)