



ard f.lli raccanello s.p.a.

industria vernici e smalti

TECHNICAL SHEET N° 43

CODE 7.352.5315

stucco riempitivo murale

Fibre reinforced stucco paste for interiors & exteriors

GENERAL PROPERTIES

STUCCO RIEMPITIVO MURALE is a white spatulable stucco based on particular acrylic resins and silicate fillers with a special grading curve. It provides an optimal workability and reduced shrinkage.

The remarkable filling properties make STUCCO RIEMPITIVO MURALE an extremely versatile product. It is particularly suitable for exterior stucco work with synthetic painting cycles, when treating residential/industrial buildings.

INSTRUCTIONS

Substrate preparation:

Ensure the substrate has weathered for at least 28 days (necessary to guarantee full carbonation). STUCCO RIEMPITIVO MURALE should be applied on substrates which are perfectly dry, weathered and solid.

Apply a hand of ISOLEX W or ISOLEX - consolidating insulator – if the cavity is chalky.

Preventively reduce the depth of any holes (more than 1cm deep) by filling with tiny brick fragments.

Application:

- Use neat (further dilution is not required). Stir well and use a spatula or float to apply the product on the substrate imperfections. Fill as many times as necessary to obtain a smooth surface.
- Do not apply on sun drenched surfaces or at ambient temperatures below +5°C. After application, protect the treated surfaces against driving rain for at least 24 hrs.
- Wash equipment immediately after use with water.
- Store in cool, frost free premises.
- Use the products in compliance with the current Hygiene & Safety Regulations. Do not release the containers into the environment.

Refer to the PSDS for further details.

TECHNICAL PROPERTIES

SPECIFIC WEIGHT	1530 ± 50 g/l
VISCOSITY AT 20°C	Thixotropic paste
DRY RESIDUE % WEIGHT	87±2
COLOUR	White
DRYING (DEEP) AT 20°C & 0,5 MM	6 hrs

YIELD

One layer of STUCCO RIEMPITIVO MURALE with a 1 mm thick dry layer implies a yield of 0,7 m²/kg.

SPECIFICATIONS

FIBRE REINFORCED FILLER STUCCO FOR WALL SURFACES

Application on pre-treated walls of spatulable filler stucco based on acrylic binders in aqueous emulsion and silicate fillers with a special grading curve & reduced shrinkage, type STUCCO RIEMPITIVO MURALE, with a consumption of 1,25 kg/m² per mm thickness.

€/m².

The data herein were correct at the time of Quality Control and refer to standardized environmental conditions. The same are to be considered as a guide.
Revision 2017/07



ard · f.lli raccanello s.p.a. · industria vernici e smalti

35129 PADOVA – Zona Ind.le Nord 1ª Strada, 13 – Tel. 049.8060000 (5 linee)
Fax 049.773749 – www.ard-raccanello.it - E-mail: ardspa@ard-raccanello.it