



# ard f.lli raccanello s.p.a. industria vernici e smalti

TECHNICAL DATA **50**

CODE 0.523.1010

## **pareti mobili**

Emulsion paint for plasterboard

### **GENERAL PROPERTIES**

PARETI MOBILI is a quality emulsion paint which features a remarkable covering power & optimum "grade" of white.

The extraordinary applicability makes it particularly suitable for application directly on "difficult" surfaces such as chalk, plasterboard, civil lime plaster & substrates characterized by porosity & excessive absorption.

Easy to use - PARETI MOBILI - offers exceptional brushability, good spreading & reduced "dripping".

The remarkable breathability impedes the formation of condensation as the water vapour "migrates" from the inside to the outside.

PARETI MOBILI is odourless and produces an aesthetically smooth matt finish. A versatile product which meets the expectations of professionals & the most demanding applicators.

### **INSTRUCTIONS**

#### **Substrate preparation:**

- Bare interior walls: brush accurately removing dust, filth & unsound plaster. Level imperfections (holes, cracks etc.) with LITOSTUCCO 1.050.1010 filling as necessary. Allow 24 hrs, ensure the wall is perfectly dry. Plasterboard surfaces do not require sealing therefore, finish directly with PARETI MOBILI.  
Treat particularly chalky surfaces with a hand of ISOLEX W, ARDFIX diluted (1 part in 8 parts of water) or BIANCOFIX. Allow at least 4 hrs & apply two hands of PARETI MOBILI.
- Interior walls painted with "breathable" paints: clean accurately & stucco imperfections with LITOSTUCCO as indicated above.
- Interior walls painted with washable emulsion paints: clean the surface, stucco any imperfections, sand, dust & seal the stuccoed areas with a layer of ISOLEX W or ARDFIX diluted with water. Allow at least 4 hrs & proceed with PARETI MOBILI.

## Application:

Apply PARETI MOBILI as follows:

- Roller application: stir well, dilute at 10-20% in water volume & apply uniformly cross-wise. Allow at least 6 hrs & apply the second hand.
- Brush: stir well, dilute at 15-25% in water volume & apply by brushing cross-wise. Allow at least 6 hrs and apply the second hand.
- Brush application is suitable for substrates with poor absorption such as cement plaster, sealed primers & non-chalky emulsion paints.
- Store in cool premises above freezing. Wash equipment immediately after use with water.
- Do not apply at ambient or substrate temperature below + 5°C or above + 35°C.
- Use in compliance with the current Health & Safety Regulations. Dispose of spent material/containers according to the same.
- Refer to the PSDS for further information.
- PARETI MOBILI is compatible with the 16COLOURS & WIZARD tinting systems.

## TECHNICAL DATA

SPECIFIC WEIGHT	<b>1500 ± 50 g/l</b>	
VISCOSITY AT 20°C	<b>6.000 ± 1.000 cP</b>	
ASPECT	<b>Matt</b>	
COLOUR	<b>White</b>	
WASH RESISTANCE (EN 13300)	<b>Class 3</b>	
DRYING AT 20°C	TOUCH DRY	<b>2 hrs</b>
	THROUGH DRYING	<b>24 hrs</b>

## YIELD

Approx 5,3 m<sup>2</sup>/l with a 2 layer painting cycle. Coverage is more extensive on rough substrates.

## TENDER SPECIFICATION ITEM

INTERIOR TRANSPIRING EMULSION PAINT SPECIFIC FOR PLASTERBOARD

Application on pretreated mural surfaces of two layers of low odour emulsion paint with optimum spreading & covering power type PARETI MOBILI with a minimum consumption of 0,19 l/m<sup>2</sup>.

€/m<sup>2</sup>

The data herein were correct at the time of Quality Control and refer to standardized environmental conditions. The same are to be considered as a guide.  
Revision 2015/06.



**ard · f.lli raccanello s.p.a. · industria vernici e smalti**

35129 PADOVA – Zona Ind.le Nord 1<sup>a</sup> Strada, 13 – Tel. 049.8060000 (5 linee)  
Fax 049.773749 – www.ard-raccanello.it - E-mail: assistenza@ard-raccanello.it