



ard f.lli raccanello s.p.a. industria vernici e smalti

TECHNICAL SHEET **72**

CODE 0.548.1010

ard interni

Professional emulsion paint with optimum covering-power

GENERAL PROPERTIES

ARD INTERNI is an aesthetically pleasing professional emulsion paint for interiors. It offers a remarkable performance, excellent "whiteness", covering power, vapour permeability, anti-reflection, flow & smooth touch.

INSTRUCTIONS

Substrate preparation:

- Bare interior surfaces: clean thoroughly and remove any unsound plaster using a broomcorn brush. Level any imperfections (holes, cracks, fissures etc) with LITOSTUCCO 1.050.1010 applying as many times as necessary. Allow 6 hrs, sand the stuccoed areas and clean thoroughly.
- The choice of sealer depends on the conditions of the substrate. ISOLEX W or ARDFIX are suitable in most cases. Use BIANCOFIX 0.079.1010 (fixative hiding sealer) on particularly dark surfaces. Allow to dry and apply 2 hands of ARD INTERNI.
- Interior walls with distemper paintwork: clean thoroughly and stucco any imperfections with LITOSTUCCO (as indicated above). Sand & seal the stuccoed areas with ARDFIX. If the substrate is unsound or chalky treat the whole surface with ISOLEX W. Allow 4 or 12 hrs respectively before applying ARD INTERNI.
- Interior walls with washable emulsion paintwork: clean thoroughly, stucco any imperfections, sand and dust. Seal the stuccoed areas with a hand of ARDFIX. Allow 4 hours & apply ARD INTERNI.

Application:

Apply ARD INTERNI as follows:

- Brush: stir well, thinning at 45-55% in water volume by cross-brushing. Allow 1-2 hrs and apply the second hand, thinning ARD INTERNI at 40-50% in water volume.
- Roller: thin at 25-35% in water volume.
- ARD INTERNI can be easily tinted with the high concentration colorants ARD COLOR 2.950, the universal colorants COLORATUTTO 0.951 & IDROPAINT 0.502.

- Store in cool, frost free premises.
- Wash equipment immediately after use with water.
- Do not apply at ambient/substrate temperature below +5°C or above +35°C.
- Use in compliance with the current Health & Safety Regulations. Dispose of spent material/containers according to the same.

Refer to the PSDS for further details:

TECHNICAL PROPERTIES	SPECIFIC WEIGHT	1730 ± 50g/l	
	VISCOSITY AT 20°C	24.000 ± 2000 cP	
	ASPECT OF FILM	Matt	
	COLOUR	White	
	DRYING	TOUCH DRY	1,5 hrs
		THROUGH DRYING	24 hrs

YIELD 2 layers imply a yield of 4,5-5 m²/l. We recommend testing on the specific surface.

**TENDER
SPECIFICATION ITEM**

**PROFESSIONAL EMULSION PAINT WITH OPTIMUM COVERING
POWER**

Two coat application of emulsion paint with optimum covering power for interiors based on synthetic copolymers & hiding pigments like ARD INTERNI with a minimum consumption of 0,21 l/m².

€/m²

The data herein were correct at the time of Quality Control and refer to standardized environmental conditions. The same are to be considered as a guide.

Revision 2015/06



ard · f.lli raccanello s.p.a. · industria vernici e smalti

35129 PADOVA – Zona Ind.le Nord 1ª Strada, 13 – Tel. 049.8060000 (5 linee)
Fax 049.773749 – www.ard-raccanello.it - E-mail: ardsipa@ard-raccanello.it