



# ard f.lli raccanello s.p.a. industria vernici e smalti

TECHNICAL SHEET **74**

CODE 0.525.

## **interior**

Washable latex paint for interiors

### GENERAL PROPERTIES

INTERIOR is a latex paint developed from innovative formulation criteria. It offers an optimum "whiteness", good hiding power & washability. The special synthetic polymers in emulsion provide a good scrub resistance, ease of application & flow.

These features together with an appealing matt effect make INTERIOR a quality finish for interiors.

### INSTRUCTIONS

#### Substrate preparation:

- Bare interior walls: use a soft brush to remove dust & unsound plaster. Level any imperfections (holes, cracks or fissures), with LITOSTUCCO or SILVER STUCK (powder stucco) adding as many times as necessary. Allow 6 hrs, sand the stuccowork & clean accurately. Seal the whole surface with a hand of thinned ISOLEX W or ARDFIX (1 part in 8 parts of water). Allow 4 or 12 hrs respectively & apply 2 hands of INTERIOR.
- Interiors with distemper paintwork: clean accurately & stucco any imperfections with LITOSTUCCO as indicated above. Sand & seal the whole surface with a hand of ISOLEX W or ARDFIX. Allow 12 hrs & apply INTERIOR.
- Interiors with washable latex paintwork: clean accurately, stucco any imperfections, sand & dust. Seal the stucco work with a hand of ARDFIX. Allow 4 hrs & proceed with INTERIOR.

#### Application:

Apply INTERIOR as follows:

- Brush: stir well, dilute at 35-40% in water volume & apply by criss-cross brushing. Allow 2-3 hrs & proceed with the second hand thinning INTERIOR at 30-35% in water volume.
- Roller: dilute at 20-25% in water volume.
- INTERIOR is easy to tint using IDROPAINT 502, high concentration colorants, COLORATUTTO 0.951 & ARDCOLOR 2.950.
- Do not apply at a temperature below +5°C or above +35°C.
- Wash equipment immediately after use with water.
- Store in cool, frost free premises.
- INTERIOR is compatible with the 16COLOURS & WIZARD tinting systems.

- Use products in compliance with the current Health & Safety Regulations. Dispose of spent material/containers according to the same.
- Refer to the PSDS for further details.

---

## TECHNICAL PROPERTIES

SPECIFIC WEIGHT	<b>1640 ÷ 50 g/l</b>	
VISCOSITY AT 20 °C	<b>12.500 ± 2000 cP</b>	
ASPECT OF FILM	<b>Satiny</b>	
COLOUR	<b>White</b>	
DRYING AT 20 °C	TOUCH DRY	<b>2 hrs</b>
	THROUGH DRYING	<b>24 hrs</b>
WASH RESISTANCE	EN 13300	<b>Class 3</b>

---

## YIELD

A two coat cycle implies a yield of 5 - 5,5 m<sup>2</sup>/l.

---

## TENDER SPECIFICATION ITEM

### WASHABLE LATEX PAINT

Application on treated surfaces of two layers of highly covering emulsion paint based on synthetic copolymers in aqueous dispersion & colouring pigments type INTERIOR, with a min consumption of 0,19 l/m<sup>2</sup>.

€/m<sup>2</sup>

---

The data herein were correct at the time of Quality Control & refer to standardized environmental conditions. The same are to be considered as a guide.

Revision 2014/10



**ard · f.lli raccanello s.p.a. · industria vernici e smalti**

35129 PADOVA – Zona Ind.le Nord 1ª Strada, 13 – Tel. 049.8060000 (5 linee)  
 Fax 049.773749 – www.ard-raccanello.it - E-mail: [ardspa@ard-raccanello.it](mailto:ardspa@ard-raccanello.it)