



ard f.lli raccanello s.p.a. industria vernici e smalti

TECHNICAL SHEET **202**

CODE 0.539

ardsalus lavabile

VOC free super-washable odourless latex paint

GENERAL PROPERTIES

The ARDSALUS line is formulated with non toxic raw materials in order to respect the environment & protect the health of those living/working in painted premises. This line offers products which are odourless as they are free of solvents, plasticizers & heavy metals. ARDSALUS LAVABILE is a top quality innovative water-paint which offers excellent scrub/water-wash resistance together with a refined velvety matt effect.

ARDSALUS LAVABILE flows perfectly offering a remarkable covering power & whiteness. Its ideal for the painting of rooms intended for a long-term stay, such as domestic environments (especially if the occupants are allergic).

INSTRUCTIONS

Substrate preparation:

- Bare interior walls: remove dust & unsound plaster with a soft brush. Level imperfections with LITOSTUCCO 1.050.1010 filling as required. Allow 6 hrs, sand stuccoed areas and clean thoroughly.
- Apply ARDSALUS ISOLANTE (dilution depends on the condition of the substrate). Allow to dry & apply two layers of ARDSALUS LAVABILE.
- Surfaces painted with washable latex paints: clean thoroughly, stucco imperfections sand & dust. Seal the stuccoed areas with a layer of ARDSALUS ISOLANTE. Allow 4 hrs and proceed with ARDSALUS LAVABILE.

Application:

Apply ARDSALUS as follows:

- Brush: stir well, dilute at 35-40% in water volume. Stir & apply in a criss-cross fashion. After 3 hrs proceed with the second hand diluting at 30-35 in water volume.
- Roller: dilute at 25-30% in water volume.
- ARDSALUS LAVABILE can be coloured using the 16 COLOURS tinting system' s colouring pastes.
- Do not apply at ambient or substrate temperature below +5°C or above +35°C.

- Wash equipment immediately after use with water.
- Store in cool, frost free premises.
- Use in compliance with the current Health & Safety Regulations. Dispose of spent material/containers according to the same.
- Refer to the PSDS for further details.

TECHNICAL PROPERTIES

SPECIFIC WEIGHT		1470 ± 50 g/l
VISCOSITY AT 20°C		10.000 ± 1000 cP
ASPECT OF FILM		Matt
COLOUR		White
DRYING AT 20 °C	TOUCH DRYING	2 hrs
	THROUGH DRYING	24 hrs
WASH RESISTANCE	EN 13300	Class 1

YIELD

A two layer cycle implies a yield of about 6 m²/l. Such yield refers to smooth surfaces with medium absorption. It is best to determine the same by testing.

TENDER SPECIFICATION ITEM

VOC FREE SUPER WASHABLE ODOURLESS LATEX PAINT

Application on prepared mural surfaces of two layers of odourless latex paint, free of any solvents/hazardous substances, for interiors-exterior type ARDSALUS LAVABILE with a minimum consumption of 0,17 m²/l.

€/m²

The data herein were correct at the time of Quality Control and refer to standardized environmental conditions. The same are to be considered as a guide.

Revision 2014/10



ard · f.lli raccanello s.p.a. · industria vernici e smalti

35129 PADOVA – Zona Ind.le Nord 1ª Strada, 13 – Tel. 049.8060000 (5 linee)
Fax 049.773749 – www.ard-raccanello.it - E-mail: ardspace@ard-raccanello.it