



ard f.lli raccanello s.p.a. industria vernici e smalti

TECHNICAL SHEET **58**

CODE 0.507

movida

Solvent free washable emulsion paint for interiors

GENERAL PROPERTIES

MOVIDA is a high performing odourless wall paint devised to protect the health of those living/working in painted premises & the environment in general. It is free of solvents, plasticizers, heavy metals & harmful substances.

MOVIDA lends a remarkable wash resistance, water vapour permeability, optimum covering power & whiteness.

MOVIDA flows perfectly so it is easy to apply & offers a refined velvety matt effect.

INSTRUCTIONS

Substrate preparation:

- Bare indoor walls: remove dust & unsound plaster with a soft brush. Level imperfections with LITOSTUCCO 1.050.1010 filling as required. Allow 6 hrs, sand the stuccoed areas & clean thoroughly.
- Apply ARDSALUS ISOLANTE or ARDFIX (dilution depends on the condition of the substrate). Allow to dry & apply two layers of MOVIDA.
- Surfaces painted with washable emulsion paints: clean thoroughly, stucco imperfections sand & dust. Seal the stuccoed areas with a layer of ARDSALUS ISOLANTE or ARDFIX. Allow 4 hrs and proceed with MOVIDA.

Application:

Apply MOVIDA as follows:

- Brush: stir well, dilute at 35-40% in water volume. Stir again thoroughly & apply crosswise. After 3 hrs proceed with the second hand diluting at 30-35% in water volume.
- Roller: dilute at 25-30% in water volume. Roller application is recommended when using medium or dark hues.
- MOVIDA is compatible with the 16 COLOURS & WIZARD tinting systems.

- Do not apply at ambient or substrate temperature below +5°C or above +35 °C.
- Wash equipment immediately after use with water.
- Store the product in a cool place, above freezing.
- This product does not require a "WARNING" label.
- Use in compliance with the current Health & Safety Regulations. Dispose of spent material/containers according to the same.
- Refer to the PSDS for further information.

TECHNICAL PROPERTIES

SPECIFIC WEIGHT		1550 ± 50 g/l
VISCOSITY AT 20°C		15.000 ± 1500 cP
ASPECT OF FILM		Matt
WASH RESISTANCE	EN 13300	Class 2
COLOUR		White
DRYING AT 20 °C	TOUCH DRYING	2 hrs
	THROUGH DRYING	24 hrs

YIELD

A two layer cycle implies a yield of about 6 m²/l. Such yield refers to smooth surfaces with medium absorption. However, it is best to determine the same by testing.

TENDER SPECIFICATION ITEM

ODOURLESS SOLVENT FREE WASHABLE EMULSION PAINT

Application on prepared mural surfaces of two layers of odourless emulsion paint for interiors, free of any solvents/harmful substances, type MOVIDA with a minimum consumption of 0,17 m²/l.

€/m²

The data herein were correct at the time of Quality Control and refer to standardized environmental conditions. The same are to be considered as a guide.
Revision 2012/07



ard · f.lli raccanello s.p.a. · industria vernici e smalti

35129 PADOVA – Zona Ind.le Nord 1ª Strada, 13 – Tel. 049.8060000 (5 linee)
Fax 049.773749 – www.ard-raccanello.it - e-mail: ardspa@ard-raccanello.it