



ard f.lli raccanello s.p.a. industria vernici e smalti

TECHNICAL SHEET **60/2**

CODE 0.526.

a-b paint traspirante

Breathable mould resistant emulsion paint for interiors

GENERAL PROPERTIES

A-B PAINT TRASPIRANTE is suitable for painting interior walls which require an effective protection against fungi & moulds.

A-B PAINT TRASPIRANTE features good hiding power, optimum substrate adhesion, brushability & flow.

Its ideal for environments with a high concentration of water vapour such as kitchens, bathrooms, greenhouses etc., as it boasts a remarkable breathability.

INSTRUCTIONS

Substrate preparation:

- Bare walls: brush thoroughly to remove any filth and unsound plaster. Level any imperfections with LITOSTUCCO 1.050.1010, adding as many times as necessary.
Allow 6 hours, sand repair areas & clean thoroughly.
The choice of sealer depends on the condition of the substrate, ARDFIX 0.070. is fine in most cases. Apply ISOLEX W on unsound surfaces & BIANCOFIX (fixative hiding sealer) on particularly dark surfaces. Ensure the surface is dry & apply two coats of A-B PAINT TRASPIRANTE.
- Interior walls affected by mould: apply ready ARDSAN RISANANTE MURALE 0.916.0000 on the infested areas.
- Allow 12 hours and brush the surface accurately. Stucco any imperfections with LITOSTUCCO as described above. If sealing is required after sanding use ARDFIX 0.070 diluted correctly.

Application:

Apply A-B PAINT TRASPIRANTE as follows:

- Brush: stir well; thin at 55-60% in water volume and apply by cross-brushing. Allow three hours & apply the second coat.
- Roller: thin at 50-55% in water volume.
- Store in cool premises, above freezing.
- Keep out of the reach of children and pets.
- Do not contaminate food, drinks or watercourses.
- Ensure the room is "aired" correctly during and after application.
- Do not apply with ambient or substrate temperature below +5°C or above + 35°C. Avoid applying in direct sunlight.

- Wash hands etc. with soap and water after handling the product.
- Wash equipment with water.
- A-B PAINT TRASPIRANTE is easy to tint with IDROPAINT 0.502. or with the universal COLORATUTTO colorants.
- We recommend “soft” colours, which require a small amount of colorants, in order to avoid altering the product’s restorative properties.
- A-B PAINT TRASPIRANTE is compatible with the 16COLOURS & WIZARD tinting systems.
- Use products in compliance with the current Health & Safety Regulations. Do not release containers to the environment after use.
- Refer to the PSDS for further details.

TECHNICAL PROPERTIES

SPECIFIC WEIGHT	1620 ± 50 g/l	
VISCOSITY AT 20 °C	16000 ± 1000 cps	
APPEARANCE OF FILM	matt	
DRYING AT 20 °C	TOUCH DRY	2 hrs
	THROUGH DRYING	24 hrs

YIELD

The two-coat painting cycle implies a yield of approx. 5-5,5 m²/l.

TENDER SPECIFICATION ITEM

BREATHABLE RESTORATIVE DISINFECTING EMULSION PAINT

Brush or roller application on pretreated surfaces of breathable mould resistant paint based on synthetic copolymers in aqueous dispersion, colorants & inert fillers, suitable for painting interiors requiring an effective protection against fungi and moulds with a minimum consumption of 0.2 l/m²

€/m²

The data herein were correct at the time of Quality Control & refer to standardized environmental conditions. The same are to be considered as a guide.

Revision 2015/06



ard · f.lli raccanello s.p.a. · industria vernici e smalti

35129 PADOVA – Zona Ind.le Nord 1^a Strada, 13 – Tel. 049.8060000 (5 linee)

Fax 049.773749 – www.ard-raccanello.it - E-mail: ardsipa@ard-raccanello.it