



ard f.lli raccanello s.p.a. industria vernici e smalti

TECHNICAL SHEET **63**

CODE 0.531.

spring

Breathable hiding interior emulsion paint

GENERAL PROPERTIES

SPRING is a breathable paint featuring a good “whiteness”, covering power, brushability and flow.

It is ideal as a finish for interiors.

INSTRUCTIONS

Substrate preparation:

- Bare interior walls: use a common millet brush to remove dust, filth & unsound plaster. Level imperfections (holes, cracks or fissures) with LITOSTUCCO 1.050.1010, filling as many times as necessary. Allow 6 hrs & ensure the wall is perfectly dry.
The choice of sealer depends on the condition of the substrate ARDFIX is fine in most cases. Use BIANCOFIX 0.079 fixative covering sealer on particularly dark surfaces. Allow the surface to dry & apply two coats of SPRING.
- Interior walls with sound distemper paintwork: clean thoroughly, stucco any imperfections with LITOSTUCCO, proceeding as described above. After sanding, seal the stuccoed areas with ARDFIX. If the substrate is particularly chalky or decaying treat the whole surface with ARDFIX. Allow 4 or 12 hrs respectively & apply SPRING.
- Interior walls with washable emulsion paintwork: clean the surface thoroughly. Stucco any imperfections, sand and dust. Seal repair areas with a coat of ARDFIX. Allow 4 hours & apply SPRING.

Application:

Apply SPRING as follows:

- Brush: stir well, thin at 60-65% in water volume and apply by cross-brushing. Allow 1-2 hrs & proceed with the second coat, thinning SPRING at 55-60% in water volume.
- Roller: thin at 50% in water volume.
- SPRING is easy to tint using: IDROPAINT 0.502, high concentration ARDCOLOR 2.950 colorants & the universal 0.951 COLORATUTTO colorants.
- Store the product in cool premises; under frost proof conditions.
- Wash tools immediately after use with water.

- Do not apply at ambient or substrate temperature below +5°C or above +35°C. Avoid applying in direct sunlight.
- The product does not require a WARNING label. Use in compliance with the current Health & Safety regulations. Dispose of spent material/containers according to the same.

Refer to PSDS for further information.

TECHNICAL PROPERTIES

SPECIFIC WEIGHT	1700 ± 50 g/l	
VISCOSITY AT 20 °C	17000 ± 1000 cP	
ASPECT	Matt	
COLOUR	White	
DRYING AT 20 °C	TOUCH DRY	1,5 hrs
	THROUGH DRYING	24 hrs

YIELD

A two-coat painting cycle implies a yield of approx 4,5 – 5 m²/l. Said yield refers to smooth surfaces with medium absorption. We recommend testing to determine the same.

TENDER SPECIFICATION ITEM

BREATHABLE HIDING EMULSION PAINT FOR INTERIORS

Two coat application on pretreated interior walls of breathable hiding emulsion paint for interiors based on synthetic copolymers in aqueous dispersion & covering pigments type SPRING with a min consumption of 0,23 l/m².

€/ m²

The data herein were correct at the time of Quality Control and refer to standardized environmental conditions.
The same are to be considered as a guide.
Revision 2012/07



ard · f.lli raccanello s.p.a. · industria vernici e smalti

35129 PADOVA – Zona Ind.le Nord 1^a Strada, 13 – Tel. 049.8060000 (5 linee)

Fax 049.773749 – www.ard-raccanello.it - E-mail: ardspa@ard-raccanello.it