



# ard f.lli racca nello s.p.a. industria vernici e smalti

TECHNICAL SHEET **69**

CODE 0.506

**maison**

Washable latex paint for interiors & exteriors

## GENERAL PROPERTIES

MAISON is a high performing wall paint which offers optimum wash resistance, refinishing, covering power, whiteness & water vapour permeability.

MAISON flows perfectly so it is easy to apply & offers a refined velvety matt effect.

MAISON is an extremely versatile product devised for painting two coat plaster work, precast panels, plaster of Paris & plasterboard.

## INSTRUCTIONS

### Substrate preparation:

- Bare interior walls: remove dust & unsound plaster with a soft brush. Level imperfections with LITOSTUCCO 1.050.1010 filling as required. Allow 6 hrs, sand the stuccoed areas & clean thoroughly.
- If the surface is not particularly chalky, apply 2 hands of MAISON directly. Otherwise, pretreat the surface by applying ISOLEX W or ARDIFX -thinning according to the conditions of the substrate -.
- Interior surfaces with washable latex paintwork: clean thoroughly, stucco imperfections sand & dust. Seal the stuccoed areas with a layer of ARDIFX. Allow 4 hrs and proceed with MAISON.

### Application:

Apply MAISON as follows:

- Brush: stir well, dilute at 35-40% in water volume. Stir again thoroughly & apply in a criss-cross fashion. Allow 3 hrs & proceed with the second hand diluting at 30-35% in water volume.
- Roller: dilute at 25-30% in water volume. Roller application is recommended when using medium or dark hues. Do not thin above 20% when applying on plaster of Paris or plasterboard.
- MAISON is compatible with the 16 COLOURS & WIZARD tinting systems.
- Do not apply at ambient or substrate temperature below +5°C or above +35°C.
- Wash equipment immediately after use with water.

- Store in cool, frost free premises.
- Use in compliance with the current Health & Safety Regulations. Dispose of spent material/containers according to the same.
- Refer to the PSDS for further information.

---

## TECHNICAL PROPERTIES

SPECIFIC WEIGHT		<b>1580 ± 50 g/l</b>
VISCOSITY AT 20°C		<b>12.000 ± 1500 cP</b>
ASPECT OF FILM		<b>Matt</b>
WASH RESISTANCE	EN 13300	<b>Class 2</b>
COLOUR		<b>White</b>
DRYING AT 20 °C	TOUCH DRYING	<b>2 hrs</b>
	THROUGH DRYING	<b>24 hrs</b>
WATER VAPOUR PERMEABILITY	EN ISO 7783-1&2	<b>Class V<sup>1</sup> (high)</b>

---

## YIELD

A two layer cycle implies a yield of about 7 m<sup>2</sup>/l. Such yield refers to smooth surfaces with medium absorption. However, it is best to determine the same by testing.

---

## TENDER SPECIFICATION ITEM

### WASHABLE LATEX PAINT FOR INTERIORS & EXTERIORS

A two layer application on prepared surfaces of washable latex paint for interiors & exteriors type MAISON with a minimum consumption of 0,14 l/m<sup>2</sup>.

€/m<sup>2</sup>

---

The data herein were correct at the time of Quality Control and refer to standardized environmental conditions. The same are to be considered as a guide.  
Revision 2015/06



**ard · f.lli raccanello s.p.a. · industria vernici e smalti**

35129 PADOVA – Zona Ind.le Nord 1<sup>a</sup> Strada, 13 – Tel. 049.8060000 (5 linee)  
Fax 049.773749 – www.ard-raccanello.it - e-mail: [ardspa@ard-raccanello.it](mailto:ardspa@ard-raccanello.it)